

Technical Data for:**Mapetrol PREMIUM POWER RACING 4T 10W-40****Description:**

Mapetrol Premium Power Racing 4T 10W-40 is most advanced ester technology lubricant, designed for the latest 4-stroke motorcycle engines. It is created for the better clutch “grip” control and perfect protection of the gearbox and engine. Carefully selected esters and additives provide maximum output power, minimise wear, delivers excellent thermal stability, improve engine cleanliness, ensures minimum oil consumption. Mapetrol Premium Power Racing 4T 10W-40 shows great performance in extreme racing conditions.

Specifications and approvals:

API SN;
JASO MA-2;

Typical characteristics:

Test	Method	Unit	Results
Density at 15°C	ASTM D 4052	[g/cm ³]	0.860
Kinematic viscosity at 40°C	ASTM D445	[mm ² /s]	92
Kinematic viscosity at 100 °C	ASTM D445	[mm ² /s]	14,2
Viscosity index	ASTM D 2270	-	160
Pour point	ASTM D 97	[°C]	-39
Flash point (Cleveland)	ASTM D 92	[°C]	233
T.B.N.	ASTM D 2896	mg KOH/g	7,5

Storage:

Storage is under cover conditions. Drums should be laid horizontally, because of damage and ingress of water, it should be keep away from direct flame and direct sunlight. Recommended storage temperature: max. 50°C.

