

Technical Data for:

MAPETROL POWER ESTER 4T 10W50

Description:

Mapetrol Power Ester 4T 10W50 is the most suitable synthetic lubricant for modern 4-stroke engines, created from carefully selected additives and ester-based base oils. Powerful formulation increase engine performance and protects all lubricated parts completely. Mapetrol Power Ester 4T 10W50 ensures good friction on clutch discs to prewent slippage, reduces wear of lubrication system, excellent thermal stability thanks to synthetic and ester based components, great fluidity at low temperatures.

Specifications and approvals:

API SN JASO MA2

Typical characteristics:

7			
Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm3]	0.854
Kinematic viscosity at 40 °C	ASTM D 445	[mm2/s]	119.7
Kinematic viscosity at 100 °C	ASTM D 445	[mm2/s]	18.4
Viscosity index	ASTM D 2270	-	173
Pour point	ASTM D 97	[°C]	-45
T.B.N.	ASTM D 2896	mg KOH/g	7.3

Storage:

Storage is under cover conditions. Drums should be laid horizontally, because of damage and ingress of water, it should be keep away from direct flame and direct sunlight. Recommended storage temperature: max. 50 °C.

