

**MAPETROL PREMIUM 7000 SN 15W-40****Description:**

Mapetrol Premium 7000 SN 15W-40 is a high-quality mineral engine oil for the lubrication of gasoline passenger cars engines (multi-valve, turbo, etc.) and diesel engines, with or without turbo. Mapetrol Premium 7000 SN 15W-40 is formulated to provide protection against sludge, soot, piston deposits and also keeps the engine clean.

**Specifications and approvals:**

API SN/CH-4

ACEA A3/B4

MB 229.1/229.3

VW 502 00/505 00

VW 501 00/500 00

PSA B71 2294

RENAULT RN0700/RN0710

**Typical characteristics:**

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm <sup>3</sup> ]	0.878
Kinematic viscosity at 40 °C	ASTM D 445	[mm <sup>2</sup> /s]	107.2
Kinematic viscosity at 100 °C	ASTM D 445	[mm <sup>2</sup> /s]	14.2
Viscosity index	ASTM D 2270	-	135
Pour point	ASTM D 97	[°C]	-32
Flash point (Cleveland)	ASTM D 92	[°C]	232
T.B.N.	ASTM D 2896	mg KOH/g	10.1

**Storage:**

Storage is under cover conditions. Drums should be laid horizontally, because of damage and ingress of water, it should be keep away from direct flame and direct sunlight. Recommended storage temperature: max. 50 °C.

