

Technical Data for:**MAPETROL ATF MB 15****Description:**

Mapetrol ATF MB 15 is premium synthetic automatic transmission fluid created from carefully selected additives and very high quality base oils, for use in the Mercedes-Benz 7 speed automatic transmissions (Type 7G-Tronic Plus). This oil is mandatory for sports vehicles (NAG2FE+) and is not backwards compatible with the previous 5- and 7- speed transmissions (MB 236.10, 236.12, 236.14.). Mapetrol ATF MB 15 offers excellent anti-wear protection, high thermal and oxidative stability, very smooth gear shifting, no vibration.

Specifications and approvals:

MB 236.15

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.842
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	17.15
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	4.4
Viscosity index	ASTM D 2270	-	170
Pour point	ASTM D 97	[°C]	-54

Storage:

Storage is under cover conditions. Drums should be laid horizontally, because of damage and ingress of water, it should be kept away from direct flame and direct sunlight. Recommended storage temperature: max. 50 °C.

