

Technical Data for:**MAPETROL MULTI VEHICLE GL 4+ 75W-80****Description:**

Mapetrol Multi Vehicle GL 4+ 75W-80 is mineral transmission oil, created from carefully selected high quality base oils and additives, for nearly all manual gearboxes of passenger cars. This oil is developed to replace OEM original oils of most brands and models. Mapetrol Multi Vehicle GL 4+ 75W-80 provide proven resistance to oil degradation, anti-wear protection, very smooth gear shifting.

Specifications and approvals:

API GL-4 +	VOLVO 97310
BMW 83220309031	VW G 052 171
BMW MTF LT-2	VW G 052 726
FIAT 9.55550-MX3	VW G 052 527
FIAT 9.55550-MZ1	VW G 055 538
FORD ESD-M2C186-A	NISSAN 999MP-MTF20P
FORD WSS-M2C200-D2	PSA 9730 A2
GM 1940182	TOYOTA JWS 227
GM 1940768	HYUNDAI 02200-00130 TOD
HONDA MTF 94	LAND ROVER TYK500030
NISSAN MT-XZ	SUBARU K0321-F0090
PSA 9730 A8	MITSUBISHI MZ312644
PSA B71 2330	MB 235.10
VOLVO 97308	BMW 83 22 0 140 516
VOLVO 97309	

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.871
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	46.6
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	9.2
Viscosity index	ASTM D 2270	-	185
Flash Point	ASTM D 92	[°C]	204
Pour point	ASTM D 97	[°C]	-45

Storage:

Storage is under cover conditions. Drums should be laid horizontally, because of damage and ingress of water, it should be keep away from direct flame and direct sunlight. Recommended storage temperature: max. 50 °C.

