

Technical Data for:

**MAPETROL MULTI VEHICLE GL 5 75W-80****Description:**

Mapetrol Multi Vehicle GL 5 75W-80 is EP extreme-pressure lubricant for gear boxes formulated from high quality base oils and a customized additive package. This oil is recommended for lubrication of all hypoid transmissions and is also suitable for spiral bevel gear, worm wheels and most transaxles. Mapetrol Multi Vehicle GL 5 75W-80 provide very good low-temperature properties, resistance to oil degradation, excellent wear resistance, long transmission life.

**Specifications and approvals:**

API GL-4/GL-5 LS

MIL L 2105 C

FORD WSD-M2C200-C

MACK GO-J Plus

PSA B71 2330

**Typical characteristics:**

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm <sup>3</sup> ]	0.875
Kinematic viscosity at 40 °C	ASTM D 445	[mm <sup>2</sup> /s]	55
Kinematic viscosity at 100 °C	ASTM D 445	[mm <sup>2</sup> /s]	10.5
Viscosity index	ASTM D 2270	-	185
Flash Point	ASTM D 92	[°C]	198
Pour point	ASTM D 97	[°C]	-50

**Storage:**

Storage is under cover conditions. Drums should be laid horizontally, because of damage and ingress of water, it should be keep away from direct flame and direct sunlight. Recommended storage temperature: max. 50 °C.

