

Technical Data for:

MAPETROL ATF CVT**Description:**

Mapetrol ATF CVT is specialized, fully synthetic gear oil designed for Continuously Variable Transmissions (CVTs) with variable-speed gears. Ideal for CVTs equipped with a rigid articulated chain or a steel pull chain.

Benefits:

- High-quality synthetic base with a wide temperature range
- Ensures seamless automatic gearbox operation and minimal wear
- Advanced additives for superior chain friction, fuel savings, and prolonged component lifespan
- Excellent seal material compatibility
- Enhanced thermal stability and corrosion protection
- Effective aeration and foam resistance, along with excellent cooling properties
- Reduces noise

Specifications and approvals:

BMW 83 22 0 136 376	GM SATURN DEX-CVT	MOPAR CVTF+4
BMW 83 22 0 429 154	HONDA HMMF HCF-2	NISSAN Matic W
BMW EZL799	HONDA HMMF (Without	NISSAN NS-3
BMW EZL799A	starting clutch)	NISSAN NS-2
BMW ZF CVT V1	HONDA CVTF	NISSAN NS-1
BMW Punch EZL 799	HYUNDAI SP-CVT 1	AFNOR FRANCE Industrial
BMW Punch EZL 799A	JEEP NS-2	Hydraulic Oil
CHRYSLER CVTF+4	KIA SP-CVT 1	RENAULT ELFMATIC
VOLKSWAGEN G 052 180	MAZDA CVTF 3320	SUBARU LINEARTRONIC CVTF II
VOLKSWAGEN G 052 516	MB 236.20	SUBARU LINEARTRONIC CVTF
DAIHATSU AMMIX CVTF-DC	MB CVT28	SUBARU E-CVTF
DAIHATSU AMMIX CVT-DFE	MINI 83 22 0 136 376	SUBARU I-CVTF
DODGE NS-2	MINI 83 22 0 429 154	SUBARU CV-30
FORD CVT23	MINI EZL799	SUZUKI CVT Fluid Green 1
FORD CFT30	MINI EZL799A	SUZUKI CVT Fluid Green 2
FORD MERCON C	MINI ZF CVT V1	SUZUKI CVT Fluid NS-2
FORD MOTORCRAFT XT-7-	MINI Punch EZL 799	SUZUKI TC
QCFT	MINI Punch EZL 799A	SUZUKI CVTF 3320
FORD WSS-M2C933-A	MITSUBISHI DiaQueen CVTF-J1	TOYOTA CVT Fluid TC
GM SATURN CVTF I-Green2	MITSUBISHI DiaQueen CVTF-J4	TOYOTA CVT Fluid FE

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.85
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	36.52
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	7.02
Viscosity index	ASTM D 2270	-	155
Flash Point	ASTM D 92	[°C]	210
Pour point	ASTM D 97	[°C]	-45

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

