

Technical Data for:**MAPETROL ATF D III-G****Description:**

Mapetrol ATF D III-G is versatile, synthetic based transmission fluid suitable for diverse hydraulic systems, encompassing automatic gearboxes, power steering, and hydraulic clutches. It assures reliable performance, aligning with the stringent standards set by GM and Ford. Ideal for vehicles demanding ATF Type Dexron-III G, Dexron-II E, or FORD MERCON V quality oil.

Benefits:

- High-quality low-viscosity synthetic base for year-round performance
- Advanced additives for fuel savings, smooth shifts, and extended component life
- Exceptional thermal and chemical stability, reducing maintenance costs
- Effective corrosion protection
- Resists aeration and foam formation effectively
- Reduces noise

Specifications and approvals:

GM Dexron III-G

ALLISON C4

CATERPILLAR TO-2

FORD Mercon V

FORD ESP-M2C138-CJ

FORD ESP-M2C166-H

MB 236.1

VOITH H 55.6335.xx (G607)

ZF TE-ML 09/ML 11/ML 14

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.85
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	35.04
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	7.1
Viscosity index	ASTM D 2270	-	171
Flash Point	ASTM D 92	[°C]	216
Pour point	ASTM D 97	[°C]	-46

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

