

**Description:**

Mapetrol ATF D III-H is versatile, all-season, synthetic based ATF designed for automatic gearboxes, hydraulic systems, and more, including heavy-duty applications. It ensures smooth operation, minimizes wear, extends transmission life, and improves fuel efficiency, meeting GM and Ford standards. Recommended for passenger cars and commercial vehicles requiring Dexron-III H/G/F, Dexron-II E, or FORD MERCON V quality ATF, compatible with most automatic gearboxes produced up to 2006.

**Benefits:**

- Maintains performance in varying temperatures, ensuring effective lubrication and stability under heavy loads
- Excellent anti-friction properties
- Enhances thermal and chemical stability, reducing maintenance costs and extending transmission life
- Provides corrosion protection, prevents aeration and foam formation
- Compatible with all sealing materials, cutting spare parts costs and preventing leaks
- Reduces noise for an improved driving experience

**Specifications and approvals:**

GM Dexron III-H/III-G/III-F

ALLISON C4

CATERPILLAR TO-2

FORD Mercon V

FORD ESP-M2C138-CJ

FORD ESP-M2C166-H

MB 236.1

VOITH H 55.6335.xx (G607)

ZF TE-ML 09/ML 11/ML 14

**Typical characteristics:**

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm <sup>3</sup> ]	0.85
Kinematic viscosity at 40 °C	ASTM D 445	[mm <sup>2</sup> /s]	35.04
Kinematic viscosity at 100 °C	ASTM D 445	[mm <sup>2</sup> /s]	7.1
Viscosity index	ASTM D 2270	-	171
Flash Point	ASTM D 92	[°C]	216
Pour point	ASTM D 97	[°C]	-46

**Storage:**

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

