

Technical Data for:**MAPETROL ATF MB 15****Description:**

Mapetrol ATF MB 15 is premium, fully synthetic lubricant, carefully formulated from top-tier base oils, that is designed exclusively for the latest MB 7-speed automatic transmissions. It is recommended for sports vehicles equipped with NAG2FE+ transmissions and is not compatible with the previous 5- and 7-speed transmissions that require MB 236.10, 236.12, or 236.14 specifications.

Benefits:

- Ensures exceptional frictional durability and superior performance
- Improves fuel economy
- Significantly extends transmission life
- Ensures smooth gear shifting with no vibrations
- Demonstrates excellent thermal and oxidation stability

Specifications and approvals:

MB 236.15

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.842
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	17.3
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	4.4
Viscosity index	ASTM D 2270	-	170
Pour point	ASTM D 97	[°C]	-54

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

