

Technical Data for:

MAPETROL OIL ADDITIVE BOOSTER

Description:

Mapetrol Oil Additive Booster enhances the performance of your engine oil, extending its lifespan. It diminishes friction and lessens the effects of wear on your engine. This booster also heightens the viscosity index of the engine oil, which helps to restore compression. Assists in neutralizing harmful acids and it is formulated using top-notch base oils, polymers and additives. It is designed for gasoline, diesel, and LPG engines, whether equipped with turbochargers or not. Can be mixed with all commercially available engine oils. It boasts a non-obstructive formulation that avoids filter blockages and poses no threat to catalytic converters.

Benefits:

- Enhances the overall effectiveness of the oil
- Diminishes friction and minimizes wear
- Raises the viscosity of the engine oil, restoring compression
- Helps with neutralizing harmful acids within the crankcase
- Decreases the usage of oil

Instructions:

- Pour the entire contents of a bottle into the warmed motor oil
- After adding, drive the engine for 5 to 10 minutes for optimal blending
- Volume of oil must remain within the prescribed limits specified for your engine
- Each bottle is suitable for treating 4 to 6 liters of motor oil

Technical specification:

Colour	BROWN
Kinematic Viscosity at 100 °C [cSt]	> 35
Flash point [°C]	> 220
Density [g/cm³]	0.888
Total Base Number [mgKOH/g]	3

