

Technical Data for:

MAPETROL CLASSIC 4T 20W-50

Description:

Mapetrol Classic 4T 20W-50 is four-stroke, motorcycle engine oil that delivers a consistently smooth and stable ride due to the reliable mineral base oils and an advanced additive blend. The meticulously balanced formula is perfectly made to meet the preferences of motorcycle enthusiasts seeking ultimate riding comfort. This lubricant has been purposefully designed for use in the engines, transmissions, and wet clutches of four-stroke motorcycles.

Benefits:

- Elevated viscosity at high temperatures ensures comprehensive engine protection, even during scorching riding conditions
- Prolongs the lifespan of motorcycles by leveraging the oil's protective attributes
- Protects the original riding comfort
- The oil's extensive applicability simplifies fluid management

Specifications and approvals:

API SG JASO MA2

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm3]	0.885
Kinematic viscosity at 40 °C	ASTM D 445	[mm2/s]	158
Kinematic viscosity at 100 °C	ASTM D 445	[mm2/s]	18
Viscosity index	ASTM D 2270	-	126
Pour point	ASTM D 97	[°C]	-36
T.B.N.	ASTM D 2896	mg KOH/g	5.9

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

