

MAPETROL PROFESSIONAL LL III 5W-30**Description:**

Mapetrol Professional LL III 5W-30, approved by Volkswagen Group, is a fully synthetic, premium-performance engine oil specifically developed for modern Volkswagen Group gasoline and diesel engines with diesel particulate filters. It is designed for use in passenger cars where VW 504 00/507 00 approval is required. Thanks to long-term stability, reduced ash content and viscosity index 5W-30 this oil extends change intervals and saves fuel.

Benefits:

- Reduces fuel consumption
- Reduces CO2 emissions
- Improves engine efficiency
- Protects engine parts

Specifications:

ACEA C2, C3

API SP, SN Plus

Approvals:

Approved VW 504 00/507 00

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.85
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	64.5
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	11.6
Viscosity index	ASTM D 2270	-	177
Flash Point	ASTM D 92	[°C]	230
Pour point	ASTM D 97	[°C]	-42
T.B.N.	ASTM D 2896	mg KOH/g	8.4

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

