

Description:

Mapetrol ATF DSG is fully synthetic lubricant, made from carefully selected high-quality base oils. It is purpose-built for modern passenger cars equipped with dual clutch transmissions (DCT), ensuring seamless and trouble-free gearbox operation. Primarily designed for VAG's DSG (Direct Shift Gearbox), but it is also suitable for other 6-speed DCT transmissions, including Chrysler Powershift, Ford Powershift, Mitsubishi TC-SST, Volvo Powershift, BMW Drivelogic 7-speed, and more. Not intended for use in VW dry clutch DSG types OAM, 02M, 02Q, and 02S.

Benefits:

- Dramatically extends the lifespan of the transmission
- Ensures exceptionally smooth gear shifts with no vibrations
- Exhibits outstanding thermal and oxidation stability, resulting in prolonged oil durability

Specifications and approvals:

API GL-4	GREAT WALL GW7DCT1	PSA 9734 S2
BMW 83220306816	GREAT WALL GWM 7DCT450	PSA JWS 2271
BMW 83220397244	HONDA MTF III	RENAULT 7711579456
BMW 83220440214	HYUNDAI 04300-2N110	RENAULT 7711785243
BMW 83222147477	WDHO-1	RENAULT BOT450 EDC 6-Speed
BMW 83222148578	KIA 04300-2N110 WDHO-1	RENAULT DC4
BMW 83222148579	KUNLUN DCTF-7S	RENAULT DW5
BMW 83222167666	MB 236.21	RENAULT DW6
BMW 83222409710	MB 236.22	SINOPEC DCTF-GS
BMW 83222433157	MB 236.24	SUZUKI 99000-22B27-036
BMW DCTF-1	MB 236.25	TOYOTA JWS 2271
BMW DCTF-2	MB 239.21	TOYOTA LF
BMW DTF 1	MB SLS A0019898603	TOYOTA LV 75W MT
BMW FFL-4	MCLAREN FFL-4	VOLVO 1161520-7
BMW MTF LT-3	MINI MTF LT-3	VOLVO 1161839
BMW MTF LT-5	MITSUBISHI DIAMOND QUEEN	VOLVO BOT341 #1161838
CHERY 730DHB/DHC 7DCT300	SSTF-1	VW G 009 317
CHERY 738DHA 7DCT380	NISSAN 999MP-6TRT00P	VW G 052 171
CHERY 9009011085	NISSAN DCT FLUID	VW G 052 178
CHRYSLER 68044345EA	NISSAN GR6	VW G 052 182
DAIMLER TRUCK DTFR 13C130	NISSAN GT-R R35	VW G 052 512
FERRARI TF DCT-F3	NISSAN LV MTF-1	VW G 052 513
FIAT 9.55550-DA11	NISSAN R35 SPECIAL	VW G 052 517
FIAT 9.55550-MZ2	PORSCHE 000.043.20	VW G 052 529
FIAT 9.55550-MZ6	PORSCHE 000.043.207.29	VW G 052 529
FORD F-DC	PORSCHE 000.043.207.30	VW G 052 726
FORD WSS-M2C200-D2	PORSCHE 000.043.305.63	VW G 052 798
FORD WSS-M2C200-D3	PORSCHE 999.917.080.00	VW G 055 512
FORD WSS-M2C200-E1	PORSCHE 999.917.080.01	VW G 055 529
FORD WSS-M2C218-A1	PORSCHE 999.917.546.00	VW G 055 549
FORD WSS-M2C936-A	PORSCHE TF 0870	VW G 060 726
GM FFL-4	PSA 1618078480	VW G 070 726
	PSA 9730 A8	VW TL 521 82



Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.849
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	38.0
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	7.5
Viscosity index	ASTM D 2270	-	170
Pour point	ASTM D 97	[°C]	-50
Flash Point	ASTM D 92	[°C]	198

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

