

MAPETROL MULTI VEHICLE GL 4+ 75W-80**Description:**

Mapetrol Multi Vehicle GL 4+ 75W-80 is high-quality, semi-synthetic, transmission oil designed for use in almost all passenger car manual gearboxes. It's particularly well-suited as a replacement for specific OEM original oils, simplifying gearbox oil selection and storage. It is recommended for all hypoid transmissions and it is suitable for spiral bevel gears, worm wheels, and most transaxles in all weather conditions.

Benefits:

- Ensures exceptionally smooth gear shifting with no vibrations
- Provides robust anti-wear protection, significantly extending the lifespan of transmissions
- Demonstrates proven resistance to oil degradation, resulting in extended oil life

Specifications and approvals:

API GL-4 +	PSA B71 2330
BMW 83220309031	VOLVO 97308
BMW 83220140516	VOLVO 97309
BMW MTF LT-2	VOLVO 97310
FIAT 9.55550-MX3	VW G 052 171
FIAT 9.55550-MZ1	VW G 052 726
FORD ESD-M2C186-A	VW G 052 527
FORD WSS-M2C200-D2	VW G 055 538
GM 1940182	TOYOTA JWS 227
GM 1940768	HYUNDAI 02200-00130 TOD
HONDA MTF 94	LAND ROVER TYK500030
NISSAN 999MP-MTF20P	SUBARU K0321-F0090
NISSAN MT-XZ	MAZDA MZ312644
PSA 9730 A8	MB 235.10
PSA 9730 A2	

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.867
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	48.2
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	8.8
Viscosity index	ASTM D 2270	-	164
Flash Point	ASTM D 92	[°C]	212
Pour point	ASTM D 97	[°C]	-39

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

