

Technical Data for:

MAPETROL PREMIUM 7000 SN 10W-40

Description:

Mapetrol Premium 7000 SN 10W-40 is semi-synthetic, universal, ester-based engine oil with a hydrosynthetic foundation, designed for both petrol and diesel engines, including older models with high mileage. It is suitable for a wide range of vehicles, including passenger cars, light SUVs, minibuses, and light trucks. It is recommended for use in MB and VW engines with additional requirements for engine oils (as specified). Note that this oil is not suitable for heavy trucks or similar vehicles.

Benefits:

- Ensures optimal engine performance in all conditions: cold starts, city driving, highway cruising, high loads, and high temperatures
- Outstanding anti-wear and anti-friction properties, significantly extending engine life, even in "start-stop" driving and cold start conditions
- Effectively combats deposits and keeps engine components clean throughout the entire oil change interval
- Preserves engine power parameters throughout the entire oil change interval

Specifications and approvals:

API SN

ACEA A3/B4

MB 229.1

MB 229.3

VW 502 00

VW 505 00

VW 501 00

VW 500 00

PSA B71 2294

RENAULT RN0700

RENAULT RN0710

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.87
Kinematic viscosity at 40 °C	ASTM D 445	[mm²/s]	93.4
Kinematic viscosity at 100 °C	ASTM D 445	[mm²/s]	13.7
Viscosity index	ASTM D 2270	-	149
Pour point	ASTM D 97	[°C]	-40
Flash point (Cleveland)	ASTM D 92	[°C]	224
T.B.N.	ASTM D 2896	mg KOH/g	10.1

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

