

Technical Data for:

MAPETROL PREMIUM 7000 SN 15W-40

Description:

Mapetrol Premium 7000 SN 15W-40 is all-season, cost-effective, universal engine oil suitable for turbocharged and non-turbocharged petrol and diesel engines, including those with very high mileage, operating under diverse conditions. Designed to provide maximum protection in a wide range of vehicles, including passenger cars, light SUVs, minibuses, and light trucks. Not suitable for heavy trucks or similar vehicles.

Benefits:

- Compatible with all sealing materials, reducing the risk of leaks and ensuring the necessary oil pressure
- Lower oil consumption because of low volatility
- Ensures efficient engine performance in all conditions
- Provides long-lasting protection against wear, friction, and corrosion
- Ensures reliable lubrication of all engine components
- Excellent detergent and dispersing properties keep engine parts clean

Specifications and approvals:

API SN/CH-4 ACEA A3/B4 MB 229.1/229.3 VW 502 00/505 00 VW 501 00/500 00 PSA B71 2294 RENAULT RN0700/RN0710

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.89
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	106
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	13.8
Viscosity index	ASTM D 2270	-	131
Pour point	ASTM D 97	[°C]	-28
Flash point (Cleveland)	ASTM D 92	[°C]	228
T.B.N.	ASTM D 2896	mg KOH/g	10.4

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

