

Technical Data for:

MAPETROL PREMIUM 7000 SN 20W-50

Description:

Mapetrol Premium 7000 SN 20W-50 is top-tier engine oil ideal for use in modern 4-stroke gasoline engines (including those with multiple valves and turbochargers) and 4-stroke diesel engines, whether equipped with turbochargers or not.

Benefits:

- Ensures excellent resistance to oxidation
- Has optimal detergent and dispersion properties
- It boasts a robust oil film for superior lubrication
- Ensures engine protection and cleanliness

Specifications and approvals:

API SN/CF ACEA A3/B4 MB 229.1 VW 501 01/505 00 PSA B71 2295

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.89
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	167
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	18.3
Viscosity index	ASTM D 2270	-	122
Pour point	ASTM D 97	[°C]	-39
Flash point (Cleveland)	ASTM D 92	[°C]	222
T.B.N.	ASTM D 2896	mg KOH/g	8.5

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

