

MAPETROL PREMIUM 9000 SN 5W-40**Description:**

Mapetrol Premium 9000 SN 5W-40 is fully synthetic lubricant suitable for all gasoline and diesel engines equipped with turbochargers and direct fuel injection. Its high-quality formulation enables extended drain intervals in accordance with manufacturer-specific requirements.

Benefits:

- Exceptional low-temperature fluidity
- Minimal resistance during startup
- Outstanding thermal stability
- Extended oil drain interval

Specifications and approvals:

API SN/CF

ACEA A3/B3

ACEA A3/B4

MB 229.1

VW 502 00/505 00

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.85
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	80
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	13.8
Viscosity index	ASTM D 2270	-	178
Pour point	ASTM D 97	[°C]	-42
Flash point (Cleveland)	ASTM D 92	[°C]	222
T.B.N.	ASTM D 2896	mg KOH/g	10.1

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

