

Technical Data for:

MAPETROL PREMIUM KARTING WS2+ 2T M**Description:**

Mapetrol Premium Karting WS2+ 2T M is fully synthetic, top-tier engine oil, meticulously designed for the rigors of racing. It is engineered for engines with cast iron liner cylinders and is fortified with WS2+, delivering an unparalleled fusion of engine performance and protection.

Benefits with WS2+ enhancement:

- Reduces friction, vibrations and heat to optimize efficiency and push the boundaries of power
- WS2+ technology significantly extends the life of your engine, ensuring it can withstand the most demanding racing conditions

Specifications and approvals:

APPROVALS FIA-CIK

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.91
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	135.8
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	17
Viscosity index	ASTM D 2270	-	136
Pour point	ASTM D 97	[°C]	-38
Flash point (Cleveland)	ASTM D 92	[°C]	250

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

