

Technical Data for:

MAPETROL PREMIUM SCOOTER SYNTH 2T

Description:

Mapetrol Premium Scooter Synth 2T is fully synthetic oil specifically engineered for 2-stroke engines that operate in a wide range of conditions, from typical to extreme. It includes meticulously chosen additives to deliver excellent antiwear protection and minimize exhaust emissions, thanks to its "smokeless" technology, ensuring engine cleanliness.

Benefits:

- Ensures friction reduction
- Increases engine life duration and performance
- Formulated to go through all injector systems
- High thermal stability
- Self mixing
- Inhibits the accumulation of deposits
- Provides effective protection against corrosion

Specifications and approvals:

API TC ISO-L-EGC

Typical characteristics:

176.00.00.00.00.00.00.00.00.00.00.00.00.00			
Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.86
Kinematic viscosity at 40 °C	ASTM D445	[mm²/s]	37
Kinematic viscosity at 100 °C	ASTM D445	[mm²/s]	6.9
Viscosity index	ASTM D 2270	-	147
Pour point	ASTM D 97	[°C]	-30
Flash point (Cleveland)	ASTM D 92	[°C]	154
T.B.N.	ASTM D 2896	mg KOH/g	2.4

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.