

**MAPETROL PREMIUM SP GF-6A 5W-30****Description:**

Mapetrol Premium SP GF-6A 5W-30 is fully synthetic oil that plays a crucial role in reducing engine wear, promoting fuel efficiency, and lowering CO2 emissions. It's important to highlight that this product has been meticulously developed to meet the stringent criteria of the latest GM Dexos1 Gen 3 specification and ILSAC GF-6 A standard. This oil is well-equipped to deliver top-notch performance, meeting the latest requirements for gasoline-powered vehicles in the United States and Asia.

**Benefits:**

- Outstanding anti-wear properties, extending engine life
- Effectively combats soot and deposits, ensuring engine cleanliness
- Compatible with hybrid cars, provided they meet the OEM specifications
- Increases fuel efficiency
- Reduces CO2 emissions
- Excellent fluidity at low temperature

**Specifications and approvals:**

API SN Plus	KIA
API SN/RC	SUZUKI
API SP	MITSUBISHI
API SP/RC	TOYOTA
ILSAC GF-6A/GF-5	SUBARU
CHRYSLER MS 6395/13340	NISSAN
FIAT 9.55535-CR1	HONDA
FORD WSS-M2C945-A	LEXUS
FORD WSS-M2C946-A	TATA
FORD WSS-M2C947-A	GENESIS
FORD WSS-M2C961-A	INFINITI
GM Dexos1™ Gen 3	JAGUAR
HYUNDAI	LAND ROVER

**Typical characteristics:**

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm <sup>3</sup> ]	0.849
Kinematic viscosity at 40 °C	ASTM D 445	[mm <sup>2</sup> /s]	63.4
Kinematic viscosity at 100 °C	ASTM D 445	[mm <sup>2</sup> /s]	11
Viscosity index	ASTM D 2270	-	167
Pour point	ASTM D 97	[°C]	-39
Flash point (Cleveland)	ASTM D 92	[°C]	225
T.B.N.	ASTM D 2896	mg KOH/g	7.4

**Storage:**

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

