

Technical Data for:

MAPETROL PREMIUM SPORT 10W-60**Description:**

Mapetrol Premium Sport 10W-60 is fully synthetic lubricant, formulated from cutting-edge, top-tier base oils, meticulously designed for the lubrication of all 4-stroke gasoline engines with multiple valves, and 4-stroke diesel engines, regardless of their turbocharger configuration.

Benefits:

- Very good fluidity at low temperature
- Outstanding engine cleanliness and durability
- Shear stability
- Wear protection
- High viscosity at hot engine

Specifications and approvals:

ACEA A3/B4

API SN/CF

BMW M-MODELS

BMW LONGLIFE-01

MB 229.3

VW 501 01/505 00

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0.855
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	156
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	25
Viscosity index	ASTM D 2270	-	194
Pour point	ASTM D 97	[°C]	-36
Flash point (Cleveland)	ASTM D 92	[°C]	235
T.B.N.	ASTM D 2896	mg KOH/g	9.5

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

