

Technical Data for:

**MAPETROL PREMIUM MOTOCROSS WS2+ 2T****Description:**

Mapetrol Premium Motocross WS2+ 2T is fully synthetic engine oil, meticulously formulated and fortified with nanosized WS2+.

**Benefits with WS2+ enhancement:**

- Minimizes friction and heat, resulting in superior engine efficiency and power output
- WS2+ technology significantly extends the life of your engine, ensuring it can withstand the most demanding racing conditions
- Reduces friction and vibrations
- WS2+ ensures that your engine operates at the highest level of precision and protection

**Specifications and approvals:**

API TC  
JASO FD  
ISO-L-EGD

**Typical characteristics:**

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm <sup>3</sup> ]	0.873
Kinematic viscosity at 40 °C	ASTM D 445	[mm <sup>2</sup> /s]	47
Kinematic viscosity at 100 °C	ASTM D 445	[mm <sup>2</sup> /s]	8.8
Viscosity index	ASTM D 2270	-	169
Pour point	ASTM D 97	[°C]	-32
Flash point (Cleveland)	ASTM D 92	[°C]	129
T.B.N.	ASTM D 2896	mg KOH/g	2

**Storage:**

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.

