

**Technical Data for:**

**MAPETROL ANTI-FREEZE DIESEL**

**Description:**

Mapetrol Anti-Freeze Diesel enhances the capacity of diesel to flow smoothly in colder operating conditions. It ensures diesel fuel's winter suitability and safeguards it against the formation of crystals or freezing. It is applicable to all diesel engines, including those equipped with common rail technology, whether turbocharged or not. Designed for operation with both low and standard levels of sulfur (bio)diesel fuels. Ensures fuel is winter-safe.

**Benefits:**

- Ensures winter suitability of diesel fuel
- Prevents wax crystal formation and size increase in cold temperatures
- Guards against gel formation and fuel system blockages
- Lowers cold filter plugging point by up to 12°C, dependent on fuel composition
- Prevents wax crystal settling at the tank bottom
- Protects the fuel system from rust and corrosion

**Instructions:**

- Dosage: Varies based on formulation, ranging from 1:167 to 1:1000 liters of diesel fuel
- Add the recommended bottle contents to the fuel tank before refueling
- Use before the first signs of wax crystal build-up
- Use one bottle for each tank filling

**Typical characteristics:**

Colour	CLEAR TO HAZY
Smell	CHARACTERISTIC
Flash point [°C]	> 61
Density [g/cm <sup>3</sup> ]	0.888

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

**Storage:**

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.