

Technical Data for:

MAPETROL ATF MB 14

Description:

Mapetrol ATF MB 14 is premium, fully synthetic lubricant formulated using meticulously chosen, top-tier base oils. It is primarily designed for use in Mercedes-Benz 7-speed automatic transmissions and NAG-V Sport transmissions. We recommend using this ATF for the 7G-Tronic and 5-Speed automatic transmissions. Its unique composition and features make it unsuitable for use in other applications.

Benefits:

- Offers exceptional frictional resilience
- Delivers outstanding performance
- Significantly extends transmission life
- Very smooth gear shifting, no vibration
- Excellent thermal and oxidation stability

Specifications and approvals:

MB 236.14

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0,84–0,86
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	25-40
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	5-7
Viscosity index	ASTM D 2270	-	> 150
Pour point	ASTM D 97	[°C]	< -40
Flash point (Cleveland)	ASTM D 92	[°C]	> 180

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.