

Technical Data for:

MAPETROL ATF MB 15

Description:

Mapetrol ATF MB 15 is premium, fully synthetic lubricant, carefully formulated from top-tier base oils, that is designed exclusively for the latest MB 7-speed automatic transmissions. It is recommended for sports vehicles equipped with NAG2FE+ transmissions and is not compatible with the previous 5- and 7-speed transmissions that require MB 236.10, 236.12, or 236.14 specifications.

Benefits:

- Ensures exceptional frictional durability and superior performance
- Improves fuel economy
- Significantly extends transmission life
- Ensures smooth gear shifting with no vibrations
- Demonstrates excellent thermal and oxidation stability

Specifications and approvals:

MB 236.15

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0,84–0,86
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	15-35
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	4,5-7
Viscosity index	ASTM D 2270	-	> 160
Pour point	ASTM D 97	[°C]	< -40
Flash point (Cleveland)	ASTM D 92	[°C]	> 180

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.