

**Technical Data for:**

**MAPETROL ATF MB 17**

**Description:**

Mapetrol ATF MB 17 is fully synthetic, automatic transmission fluid features a carefully selected blend of premium base oils and a specific additive package designed to ensure the seamless operation of Mercedes-Benz automatic transmissions (Type 9G-Tronic). It represents the latest generation of ATF, tailored for use in Mercedes-Benz vehicles equipped with 9-gear automatic transmissions, providing exceptional wear protection under all operating conditions. It is recommended for use in Mercedes-Benz automatic transmissions that adhere to MB 236.17 specifications and is also compatible with the previous MB 236.16 standard.

**Benefits:**

- Demonstrates outstanding shear stability
- Exhibits high thermal and oxidative stability
- Delivers excellent protection against wear

**Specifications and approvals:**

MB 236.17

**Typical characteristics:**

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm <sup>3</sup> ]	0,84–0,86
Kinematic viscosity at 40 °C	ASTM D 445	[mm <sup>2</sup> /s]	20-30
Kinematic viscosity at 100 °C	ASTM D 445	[mm <sup>2</sup> /s]	4-6,5
Viscosity index	ASTM D 2270	-	> 160
Pour point	ASTM D 97	[°C]	< -40
Flash point (Cleveland)	ASTM D 92	[°C]	> 180

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

**Storage:**

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.