

**Technical Data for:**

**MAPETROL DIESEL ADDITIVE**

**Description:**

Mapetrol Diesel Additive serves as a versatile diesel additive, purifying the entire fuel system, boosting the cetane number and restoring power and performance. Contains a lubricity additive provide lubrication to the diesel fuel pump when using low-sulfur fuel. It is applicable to all diesel engines, including those equipped with common rail technology, whether turbocharged or not.

**Benefits:**

- Purges the complete fuel system, encompassing injectors
- Reinstates power and operational efficiency
- Enhances combustion and curtails fuel consumption
- Elevates the cetane number
- Safeguards the fuel system from corrosion
- Provides lubrication to the diesel fuel pump
- Lessens the discharge of harmful exhaust emissions

**Instructions:**

- Pour the recommended amount from the bottle into your fuel tank before refueling
- Each bottle treats 40-60 liters of diesel
- Use one bottle every 2000 km
- For sportive use, add a bottle with each tank refill

**Typical characteristics:**

|                              |                |
|------------------------------|----------------|
| Colour                       | CLEAR          |
| Smell                        | CHARACTERISTIC |
| Flash point [°C]             | > 61           |
| Density [g/cm <sup>3</sup> ] | 0.806          |

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

**Storage:**

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.