

**Technical Data for:**

**MAPETROL KARTING CHAIN LUBE WS2+**

**Description:**

Mapetrol Karting Chain Lube WS2+, fortified with WS2+, is high-viscosity spray lubricant, expertly formulated with wear, oxidation, and corrosion-resistant additives. It delivers unparalleled chain lubrication. The WS2+ additive ensures a resilient, friction-reducing film, minimizing wear under high loads for optimal karting efficiency. Precision-engineered for karting's unique challenges, Mapetrol Karting Chain Lube WS2+ guarantees enduring protection and unwavering performance in the most demanding conditions.

**Benefits:**

- Strong adhesion and durability due to high viscosity and thread formation
- WS2+ additive delivers outstanding anti-wear benefits, minimizing friction for enhanced karting efficiency
- Penetrates hard-to-reach areas effectively
- Performs well under both high loads and low speeds
- Provides corrosion protection
- Resists dirt, moisture, and saltwater
- Withstands temperatures ranging from -30 °C to +200 °C

**Instructions:**

- Clean the surface with Mapetrol Chain Cleaner to remove old residues
- Shake the spray can for 2 minutes and apply from a 25 cm distance
- Let the solvent evaporate for a well-adhering lubricating film
- Repeat at appropriate intervals based on usage and time

**Storage:**

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.