

Technical Data for:

MAPETROL PREMIUM 7000 SN 15W-40

Description:

Mapetrol Premium 7000 SN 15W-40 is all-season, cost-effective, universal engine oil suitable for turbocharged and non-turbocharged petrol and diesel engines, including those with very high mileage, operating under diverse conditions. Designed to provide maximum protection in a wide range of vehicles, including passenger cars, light SUVs, minibuses, and light trucks. Not suitable for heavy trucks or similar vehicles.

Benefits:

- Compatible with all sealing materials, reducing the risk of leaks and ensuring the necessary oil pressure
- Lower oil consumption because of low volatility
- Ensures efficient engine performance in all conditions
- Provides long-lasting protection against wear, friction, and corrosion
- Ensures reliable lubrication of all engine components
- Excellent detergent and dispersing properties keep engine parts clean

Specifications and approvals:

MB 229.1

MB 229.3

VW 501 00

VW 500 00

VW 502 00

VW 505 00

PSA B71 2294

RENAULT RN0700

RENAULT RN0710

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0,85-0,95
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	100-120
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	12,5-16,3
Viscosity index	ASTM D 2270	-	> 130
Pour point	ASTM D 97	[°C]	< -24
Flash point (Cleveland)	ASTM D 92	[°C]	> 210
T.B.N.	ASTM D 2896	mg KOH/g	> 9

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.