

Technical Data for:

MAPETROL PREMIUM DRIFT WS2+ 10W-60

Description:

Mapetrol Premium Drift WS2+ 10W-60 is fully synthetic lubricant, meticulously formulated with top-tier base oils enriched with the remarkable benefits of WS2+. It is designed for sports cars, competition, and high-powered engines, ensuring exceptional engine protection and longevity.

Benefits with WS2+ enhancement:

- High viscosity at hot engine
- Reduces friction, promoting enhanced fuel efficiency and extending the lifespan of engine components
- Reduces wear and tear on critical engine parts, contributing to a longer and more resilient engine life
- Ensures excellent low-temperature fluidity
- WS2+ protects vital components from harmful deposits and contaminants

Specifications and approvals:

BMW LONGLIFE-01, M-MODELS

MB 229.3

VW 501 01

VW 505 00

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0,80-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	140-170
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	21,9-26,1
Viscosity index	ASTM D 2270	-	> 190
Pour point	ASTM D 97	[°C]	< -33
Flash point (Cleveland)	ASTM D 92	[°C]	> 210
T.B.N.	ASTM D 2896	mg KOH/g	> 9

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.