

Technical Data for:

MAPETROL PREMIUM KARTING WS2+ 2T K

Description:

Mapetrol Premium Karting WS2+ 2T K is high-performance, fully synthetic engine oil for racing, specifically designed for nicasil plating cylinders. It is fortified with WS2+, delivering engine protection and performance. FIA-approved.

Benefits with WS2+ enhancement:

- Reduces friction and heat, thereby optimizing engine efficiency and achieving peak power
- Reduces friction and vibrations
- WS2+ technology significantly extends the life of your engine, ensuring it can withstand the most demanding racing conditions
- Ensures seamless gear shifts

Specifications and approvals:

APPROVALS FIA-CIK

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0,86–0,92
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	30-150
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	5-20
Viscosity index	ASTM D 2270	-	> 100
Pour point	ASTM D 97	[°C]	< -30
Flash point (Cleveland)	ASTM D 92	[°C]	> 230

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.