

Technical Data for:

MAPETROL SPARCO COMPETITION C2 5W-30

Description:

Mapetrol Sparco Competition C2 5W-30 is fully synthetic, high-performance, low-viscosity lubricant made from carefully selected high quality base oils. It is highly recommended for Peugeot and Citroën petrol and diesel engines equipped with particulate filters. It is also the preferred choice for many Japanese OEMs including Toyota, Honda, Subaru and Nissan.

Benefits:

- Increases fuel efficiency
- Outstanding engine cleanliness and durability
- Reduces CO2 emissions

Specifications and approvals:

API SN/CF

ACEA C2

FIAT 9.55535-S1

PSA B71 2290-2014

RENAULT RN0700

Typical characteristics:

Test	Method	Unit	Results
Density at 15 °C	ASTM D 4052	[g/cm ³]	0,80-0,90
Kinematic viscosity at 40 °C	ASTM D 445	[mm ² /s]	50-70
Kinematic viscosity at 100 °C	ASTM D 445	[mm ² /s]	9,3-12,5
Viscosity index	ASTM D 2270	-	> 160
Pour point	ASTM D 97	[°C]	< -30
Flash point (Cleveland)	ASTM D 92	[°C]	> 210
T.B.N.	ASTM D 2896	mg KOH/g	> 9

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

Storage:

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.