

**Technical Data for:**

**MAPETROL CLASSIC 4T 10W-40**

**Description:**

Mapetrol Classic 4T 10W-40 is four-stroke, motorcycle engine oil that guarantees a smooth and consistent riding experience due to the well-balanced mixture of mineral, synthetic base oils and the advanced additives. This lubricant has been specifically engineered for use in the engines, transmissions, and wet clutches of four-stroke motorcycles.

**Benefits:**

- Extends lifespan of motorcycles through the protective attributes of the oil
- Protects the original riding comfort
- The oil's extensive applicability simplifies fluid management

**Specifications and approvals:**

API SL  
JASO MA2

**Typical characteristics:**

| Test                          | Method      | Unit                 | Results   |
|-------------------------------|-------------|----------------------|-----------|
| Density at 15 °C              | ASTM D 4052 | [g/cm <sup>3</sup> ] | 0,80-0,90 |
| Kinematic viscosity at 40 °C  | ASTM D 445  | [mm <sup>2</sup> /s] | 90-110    |
| Kinematic viscosity at 100 °C | ASTM D 445  | [mm <sup>2</sup> /s] | 12,5-16,3 |
| Viscosity index               | ASTM D 2270 | -                    | > 140     |
| Pour point                    | ASTM D 97   | [°C]                 | < -30     |
| Flash point (Cleveland)       | ASTM D 92   | [°C]                 | > 210     |
| T.B.N.                        | ASTM D 2896 | mg KOH/g             | > 6       |

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

**Storage:**

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.