

**Technical Data for:**

**MAPETROL PREMIUM C2 5W-30**

**Description:**

Mapetrol Premium C2 5W-30 is fully synthetic, high-performance, low-viscosity lubricant made from carefully selected high quality base oils. It is highly recommended for Peugeot and Citroën petrol and diesel engines equipped with particulate filters. It is also the preferred choice for many Japanese OEMs including Toyota, Honda, Subaru and Nissan.

**Benefits:**

- Increases fuel efficiency
- Outstanding engine cleanliness and durability
- Reduces CO2 emissions

**Specifications and approvals:**

API SN/CF

ACEA C2

FIAT 9.55535-S1

PSA B71 2290-2014

RENAULT RN0700

**Typical characteristics:**

| Test                          | Method      | Unit                 | Results   |
|-------------------------------|-------------|----------------------|-----------|
| Density at 15 °C              | ASTM D 4052 | [g/cm <sup>3</sup> ] | 0,80-0,90 |
| Kinematic viscosity at 40 °C  | ASTM D 445  | [mm <sup>2</sup> /s] | 50-70     |
| Kinematic viscosity at 100 °C | ASTM D 445  | [mm <sup>2</sup> /s] | 9,3-12,5  |
| Viscosity index               | ASTM D 2270 | -                    | > 160     |
| Pour point                    | ASTM D 97   | [°C]                 | < -30     |
| Flash point (Cleveland)       | ASTM D 92   | [°C]                 | > 210     |
| T.B.N.                        | ASTM D 2896 | mg KOH/g             | > 7       |

The values provided are for informational purposes only. The exact values for a specific batch are available on the Certificate of Analysis (CoA).

**Storage:**

Please store in a well-ventilated, dry, and cool area, away from direct sunlight and out of reach of children. Additional information can be found in the safety data sheet.